

* STRUCTURAL FILL SHOULD BE MOISTURE CONDITIONED TO WITHIN ABOUT 3 PERCENT OF OPTIMUM MOISTURE CONTENT PLACED IN LOOSE, HORIZONTAL LIFTS LESS THAN 8 INCHES IN THICKNESS, AND SYSTEMATICALLY COMPACTED TO A DENSE AND RELATIVELY UNYIELDING CONDITION AND TO AT LEAST 95 PERCENT OF THE MAXIMUM DRY DENSITY, AS DETERMINED USING TEST METHOD ASTM D 1557.

SITE PLAN

SCALE: 1" = 10'-0"

EXISTING BUILDING

TREE PROTECTION FENCING REQUIRED AROUND ENTIRE DRIP LINE (THE TREE PROTECTION AREA- TPA):

- RECTANGLE AROUND HOUSE FOR AVERAGE

- FENCING MUST BE INSTALLED PRIOR TO DEMOLITION AND GROUND DISTURBANCE;

- KEPT IN PLACE FOR THE DURATION OF CONSTRUCTION; - MODIFICATIONS BY APPROVAL OF SDCI PROJECT PLANNER ONLY

- NO SOIL DISTURBANCE OR ACTIVITY ALLOWED WITHIN FENCED AREA, SUCH AS BUT NOT LIMITED TO: MATERIAL STORAGE/STOCKPILING, PARKING, DUMPING OR WASHING

- PROTECT TREES AS SHOWN ON SITE PLAN AND CSC/SOILS PLAN AND PER ARBORIST'S REPORT

TREE PROTECTION AREA SIGN

MIN FRONT YARD SETBACK (PROPOSED FRONT YARD AREA: 1190 SE

CONTRACTOR TO DOWNLOAD, PRINT, LAMINATE THE TWO-SIDED TREE PROTECTION

SIGN AND AND INSTALL PER INSTRUCTIONS ON SIGN.

(http://www.seattle.gov/dpd/cs/groups/pan/@pan/documents/web_informational/p2601202.pdf) CONTRACTOR TO INSTALL SIGN AND TREE PROTECTION MEASURES BEFORE FIRST

GROUND DISTURBANCE SITE INSPECTION.

SURFACE

CB ANDERSON ARCHITECTS PLLO

7209 Greenwood Avenue North Seattle, Washington 98103 206-782-291 Fax 782-5624

CLIENT:

12051 20th Ave NE, LLC 3726 Broadway, Suite 301 Everett, Wa 98201 (425) 212-2210

CONSULTANT: Nickerson Engineering 2221 Everett Ave #202 Everett, Wa 98201 (425) 610-4425

REGISTERED raia BAndera CRAIG BRIAN ANDERSON STATE OF WASHINGTON

fOl 12051 Se

REVISIONS:

AS SHOWI

26 JUNE 201 JOB NUMBER